

- C. No down legs or kickers of any kind.
- D. 60" max door bar length, rear bar 6" max behind driver's seat.
- E. Roll over bar permitted. May go to floor and welded to sheet metal only. Cannot be welded or bolted to roof. No farther back than 6" from rear seat.
- F. You can weld cage to door post and steering column to secure cage.
- G. Gas tank and battery must be moved, secured and covered. (1 battery only)
- H. Battery holder bolted to floor sheet metal. Limit size of battery holder. Proportioned to size of battery. Not to cover whole floorboard.
- I. Gas tank holders must be 6" from rear sheet metal point. Don't beat metal back. Secured to sheet metal or to cage (6" off floor pan)
- J. 10-gallon max fuel tank size.
- K. Steering column must have factory steering column. Quick release steering wheel ok.
- L. Simple push pull floor shifters are allowed. Cable shifters allowed also.
- M. Floor pans that are rusted out may be repaired/patched with OEM size sheet metal by bolting,zip screw or rivets to existing pan.
- N. Aftermarket brake or gas pedals allowed.

Bumpers:

- A. Bumper swaps allowed. Must be factory automobile bumper. Front & Rear bumpers can be mounted with up to (8) ½" bolts total or wired on in 4 places with #9 wire. Bumpers may be welded to shock face/flange only. One 1" tack weld allowed on TOP of shock tube. One 1 inch ONLY!! Must stay in stock location.
- B. No bolting all the way through bumpers and /or bumper shocks.
- C. Stock bumper brackets. No altering brackets, no rear brackets on front.
- D. Max bumper height is 20" no lower than 14"
- E. May slot bumper to bolt on . no adding metal. May chain or wire (3 wraps max) bumpers to secure in no more than 2 spots. One 10" long 3/8" link chain per bumper shock. One bolt t'o attach chain to frame, ½" max diameter.

Tires & Rims:

- A. Any tire allowed. No foam filled or solid tires allowed.
- B. Factory OEM style rims only. Uni-lug center's (6" max dia.) ok. No full centers, bead locks or lip guards allowed. Valve stem protectors ok.
- C. No studs in tires or screwed to rims.
- D. You can use 1" lug nuts.

Suspension: